

Hinges and pivots

Aluminum geared continuous hinges

112XY

Full mortise - narrow frame and door leaf

- For 1³/₄" doors
- Patented center loaded, interlocking bearing design
- Non-handed for custom cut lengths
- Flush mounted, no inset
- 48" Maximum door width
- Beveled or square edge doors
- Frame guidance lip is extended further for retrofit applications to cover existing heavy weight architectural hinge preps
- For doors weighing up to 450 pounds without reinforcing, 600 pounds with reinforcing

Specifications

Standard length	83", 85", 95", 119"
Standard mounting	12-24 x 3/4" Steel self drilling/self tapping Phillips-head screw hardware
Certifications	<ul style="list-style-type: none">▪ Exceeds Grade 1 ANSI/BHMA 156.26 for 150lbs and 300lbs▪ UL10C listed (90 min)

Options

EPT	Electric power transfer
TWP CON	Electrical through-wire panel with Allegion Connect

Optional mounting hardware

SECHM	Security screws - hollow metal door and frame
SECWDHM	Security screws - 1/2 wood, 1/2 hollow metal
SECWDWD	Security screws - wood door and frame
TEKSWD	1/2 Self drill, self tap 1/2 wood
WD	Wood door and frame

Finishes


BHMA	Description	Substrate	Finish
628	Clear Aluminum Anodized	Aluminum	US28
710	Dark Bronze Anodized	Aluminum	313AN
711	Black Anodized	Aluminum	315AN

Custom anodizing and painting are available, consult factory



For single door applications:

For pairs of doors see chart and general information.



5/16" Clearance for Square Edge Door
11/32" Clearance for Beveled Edge Door