Flush bolts, strikes and coordinators

Manual flush bolts

Exceptionally smooth working flush bolts with sharp, crisp lines. Double action spring design provides automatic holding of brass bolt in projected or retracted position, and assures ease of operation in conjunction with deep cup finger hole.

26

Flush bolt - 4"

- Made from polished cast brass
- Bolt tip is 5/16" diameter
- Bolt throw is 3/4"
- Bolt backset is 15/32"

S	p	e	C	if	ic	a	ti	0	n	S	
_	_	_	_	•		_	٠.	_		_	

Mounting hardware	 5 X ⁵/₈" FPHSMS 			
	 8 X ³/₄" FPHSMS 			
Dimensions				
Body size	Strike size			
(Width x Length x Depth)	(Width x Length)			
111 v 0 1/-11 v 211	15 / !! y 7 1 / .!! y 1 / !!			



262

Flush bolt - 6" square end

- Made from polished cast brass
- Bolt tip is 1/2" diameter
- Bolt throw is 1"
- Bolt backset is ¹⁵/₃₂"

Specifications

Mounting hardware	 5 X 5/8" FPHSMS
	 8 X ³/₄" FPHSMS
Dimensions	
Body size	Strike size
(Width x Length x Depth)	(Width x Length)
3/4" x 6" x 1 11/32"	7/8" x 1 ³ / ₄ "



A flush bolt with radiused bottom faceplate designed specifically for simple one-step router installation. Double action spring design provides automatic holding of brass bolt in projected or retracted position, and assures ease of operation in conjunction with deep cup finger hole.

265

Flush bolt - 6" round end

- Faceplate is polished solid brass; bolt is made from aluminum zinc alloy
- Bolt tip is 1/2" diameter
- Bolt throw is 1"
- Bolt backset is 1/2"

Specifications

	7/a" x 1 3/4"		
(Width x Length x Depth)	(Width x Length)		
Body size	Strike size		
Dimensions			
	 8 X ³/₄" FPHSMS 		
Mounting hardware	 5 X ⁵/₈" FPHSMS 		



261, 262 and 265 Finishes

•			
ВНМА	Description	Substrate	Finish
605	Bright Brass	Brass	US3
609	Satin Brass, Blackened	Brass	US5
613	Oil Rubbed Bronze	Brass	US10B
619	Satin Nickel	Brass	US15
625	Bright Chrome	Brass	US26
626	Satin Chrome	Brass	US26D

Custom finishes are available as engineering special, consult customer service.