

Latches, catches and bolts

Surface bolts

40

Surface bolt, decorative light duty

- Recommended for 1 3/8" and 1 3/4" hollow core doors or door partitions
- Concealed screw design enhances appearance and security
- Exceptional strength and durability provided by interlocking construction of heavy gauge track and rod
- Permanent stop prevents rod disengagement from track
- Tension spring holds bolt in desired position
- Track assures smooth operation and interlocks with side edges of rod to eliminate marring
- Decorative 5/8" diameter knob designed to facilitate bolt operation
- Available in 3", 4" and 6" lengths
- Units packed with wood screws
- Packed with both universal and mortise strikes

Specifications

Material substrate	Made from extruded brass
Certifications	Meets ANSI/BHMA A156.16

Dimensions

Throw	Projection	Width	Length
1 1/16"	3/4"	1 1/16"	3", 4" or 6"

Finishes

BHMA	Description	Substrate	Finish
605	Bright Brass	Brass	B3
609	Blackened Brass	Brass	B5
613	Oil Rubbed Bronze	Brass	B10B
619	Satin Nickel	Brass	B15
622	Matte Black	Brass	BLK
625	Bright Chrome	Brass	B26
626	Satin Chrome	Brass	B26D
643e/716	Aged Bronze	Brass	643e/716

For other colors, consult factory.



Universal strike



Mortise strike

253

Surface bolt, decorative heavy duty

- Recommended for 1 3/4" or larger doors
- Heavy duty, decorative bolt ideal where extra strength required
- Decorative 1 1/4" diameter knob fits well with any décor and designed to facilitate bolt operation
- Available in 8" and 12" lengths. Optional lengths available, consult factory.
- Units packed with wood screws
- Packed universal strike (US) and mortise strike (MS)

Specifications

Material substrate	Made from solid brass
Certifications	Meets ANSI/BHMA A156.16

Dimensions

Throw	Projection	Half round rod	Overall width	Length
1 1/8"	1 5/16"	5/8"	1 5/8"	8" or 12"

Finishes

BHMA	Description	Substrate	Finish
605	Bright Brass	Brass	B3
613	Oil Rubbed Bronze	Brass	B10B
626	Satin Chrome	Brass	B26D

For other colors, consult factory.



Universal strike



Mortise strike