



69 Hinge pin door stops

- Economical solution for use on low frequency, light weight, residential 3 1/2 or 4" hinged doors where the installation of a standard door stop or overhead is not desirable
- Adjustable for 70° to 100° Door Openings
- Positive slip proof adjustment
- White non-marring rubber tips
- Removable bushings accommodate 1/4" to 5/16" diameter hinge pins
- Easy installation—only a screwdriver required

Material substrate

- Made from burnished wrought steel

Available accessory items

- Replaceable white rubber tip available

Dimensions

- Base diameter: 1"
- Tip diameter: 9/16"
- Projection: 3-1/4"

Finishes

BHMA	Description	Substrate	Finish
631	Matte black	Steel	F-BLK
632	Bright brass	Steel	F3
638	Blackened brass	Steel	F5
639	Satin bronze	Steel	F10
640	Oil rubbed bronze	Steel	F10B
645	Bright nickel	Steel	F14
---	Aged bronze	Steel	F-643E/716
646	Satin nickel	Steel	F15
647	Bright nickel	Steel	F15A
651	Bright chrome	Steel	F26
652	Satin chrome	Steel	F26D

For other colors, consult factory.

A
Hinges & pivots

B
Pulls & plates

C
Flush bolts & coordinators

D
Latches, catches & bolts

E22
Stops

F
Exterior hardware

G
Miscellaneous hardware