700/U700

One-way narrow viewer (UL and non-UL models)

• 120° angle of view

Exterior hardware

Viewers

- For doors 1 3/8" to 2 1/16" thick
- Secure, tamper-resistant one-way thread installation
- Simple installation—only a 1/2" hole required
- Suggested installation height: 60" from floor

Specifications

Material substrate		ade from brass, glass lens
Certifications	•	700 meets ANSI/BHMA
	-	LIZOO moote ANCI/DUMA

- A156.16, L23173 U700 meets ANSI/BHMA A156.16, L23223
- U700 is UL10C Listed (90 min)

Available accessories

- Trim washer available, 3/4" x .032" thick
- Extensions available for thicker doors
- Privacy viewer covers to prevent viewing from outside the room
- See viewer covers/extensions in this section
- See available accessories details in the viewer covers/extensions section

One-way narrow wide angle viewer (UL and non UL models)

- 120° angle of view
- For doors 2 1/8" to 2 5/8" thick
- Secure, tamper-resistant one-way thread installation
- Simple installation—only a 1/2" hole required
- Suggested installation height: 60" from floor

Specifications

Material substrate	Made from brass, glass lens		
Certifications	•	 701 meets ANSI/BHMA A156.16, L23173 	
	•	U701 meets ANSI/BHMA A156.16, L23223	
	•	U701 is UL10C Listed (90 min)	

Available accessories

- Trim washer available, 3/4" x .032" thick
- Extensions available for thicker doors
- Privacy viewer covers to prevent viewing from outside the room
- See available accessories details in the viewer covers/extensions section

700/701 and U700/U701 Finishes

ВНМА	Description	Substrate	Finish
606	Satin Brass	Brass	B4
613*	Oil Rubbed Bronze	Brass	B10B
619*	Satin Nickel	Brass	B15
622* 625*	Matte Black	Brass	B-BLK
625*	Bright Chrome	Brass	B26
626*	Satin Chrome	Brass	B26D
_	Aged Bronze	Brass	B-643e/716

^{*}Not available on 700. For other colors, consult factory.



Dimensions External diameter

Dimensions External diameter

5/8"

