

## Hinges and pivots

### Pin and barrel continuous hinges

# 702

#### Full surface pin and barrel continuous hinge (stainless steel)

- 1/4" diameter pin with nylon self-lubricating, medical grade split bearing
- For doors weighing up to 300 pounds without reinforcing, 600 pounds with reinforcing
- Flush mounted, no inset
- 48" Maximum door width
- Non-handed for custom cut lengths
- Bevel or square edge door

#### Specifications

Standard length	83", 85", 95", 120"
Material substrate	<ul style="list-style-type: none"> <li>▪ 702 - 14 Gauge type 304 stainless steel</li> </ul>
Standard mounting hardware	<ul style="list-style-type: none"> <li>▪ #10 X 1/2" Self drilling, self tapping screws</li> <li>▪ #10 X 1" Wood screws</li> <li>▪ Cover clips</li> </ul>
Certifications	<ul style="list-style-type: none"> <li>▪ Meets ANSI/BHMA 156.26</li> <li>▪ UL10C listed (3 hour)</li> </ul>

#### Options

HT Hospital tip

#### Optional mounting hardware

SECHM	Security screws - hollow metal door and frame
SECWDHM	Security screws - 1/2 wood, 1/2 hollow metal
SECWDWD	Security screws - wood door and frame
WD	Wood door and frame

#### Finishes

BHMA	Description	Substrate	Finish
630	Satin Stainless Steel	Stainless steel	US32D



#### For single door applications:

For pairs of doors see chart and general information.

