72

Hinge pin door stop

- Economical solution for use on low frequency, lightweight, residential 3¹/₂" or 4" hinged doors where the installation of a standard door stop or overhead is not desirable
- 85° to 125° Door opening adjustments
- Designed for narrow trim installation
- White rubber bumpers shoulder on stud supports rubber through entire body for engineered cushioning
- Removable bushings accommodate ¹/₄" to ⁵/₁₆" diameter hinge pins
- Easy installation

Specifications

Specifications		Dimensions	
Material substrate	Made from cast zinc	Postlength	
		17/s"	

Finishes

BHMA	Description	Substrate	Finish
676	Matte Black	Zinc	Z-BLK
677	Bright Brass	Zinc	Z-605E
-	Blackened Brass	Zinc	Z-609E
704	Oil Rubbed Bronze	Zinc	Z-613E
-	Satin Nickel	Zinc	Z-619E
681	Bright Chrome	Zinc	Z-625E
682	Satin Chrome	Zinc	Z-626E
_	Aged Bronze	Zinc	Z-643e/716
_	White	Zinc	Z-W

For other colors, consult factory.

Available accessories

Replaceable white rubber tip

$/ \prec$

Hinge pin door stop

- Economical solution for use on low frequency, 4 1/2" hinges or above hinged doors where the installation of a standard door stop or overhead is not desirable
- 85° to 125° Door opening adjustments
- Designed for narrow trim installation
- White rubber bumpers shoulder on stud supports rubber through entire body for engineered cushioning
- Removable bushings accommodate ¹/₄" to ⁵/₁₆" diameter hinge pins

Specifications

Material substrate	Made from cast zinc	

Finishes

BHMA	Description	Substrate	Finish
677	Bright Brass	Zinc	Z-605E
704	Oil Rubbed Bronze	Zinc	Z-613E
_	Satin Nickel	Zinc	Z-619E
681	Bright Chrome	Zinc	Z-625E

For other colors, consult factory.

Available accessories

Replaceable white rubber tip

