FS1153

Plunger type door holder

- Provides a contemporary yet economical method of positive hold-open
- Spring operated plunger activates with minimal pressure, releasing instantly with a light tap on the plat-form lever
- Provides a 1 5/8" throw for all types of doors
- Ribbed grey non-marring rubber shoe is securely fastened to unit with a screw and is easily replaced when worn
- Packed with fasteners for wood applications

Specifications

Material substrate	Made from cast aluminum
Certifications	Meets ANSI/BHMA 156.16, L11401

Dimensions

Height	Width	Depth	
5 ¹ / ₂ "	2"] 1/4"	

FS452 and FS455 Finish - aluminum

BHMA	Description	Substrate	Finish
628	Satin Aluminum	Aluminum	US28

For other colors, consult factory.

Available accessories

Replaceable grey non-marring rubber shoes

FS1154

Plunger type door holder

- Plunger and internal parts are plated steel and provides a 1¹/₄" throw for all types of doors
- Plunger is easily activated with minimal pressure, releasing instantly with a light tap on the platform lever
- Round non-marring rubber shoe is securely fastened with a screw in flanged cup to prevent movement or loss (when worn, shoes are easily replaced)
- Packed with fasteners for wood applications

Specifications

Material substrate	Made from cast brass
Certifications	Meets ANSI/BHMA 156.16, L31401

Dimensions

Height	Width	Depth	
61/4"	1 1/2"	1 ⁷ / ₁₆ "	

Finishes

BHMA	Description	Substrate	Finish
605	Bright Brass	Brass	US3
606	Satin Brass	Brass	US4
612	Satin Bronze	Brass	US10
613	Oil Rubbed Bronze	Brass	US10B
625	Bright Chrome	Brass	US26
626	Satin Chrome	Brass	US26D

For other colors, consult factory.

Available accessories

Replaceable grey non-marring rubber shoes





Latches, catches

Door stops, holders

Exterior

and silencers

bolts

and