### Latches, catches and bolts

Roller latches

# RL30/RL30A

### **Roller latch**

- Recommended for higher traffic applications
- Actuation is simple,  $\bar{\text{closing}}$  of the door causes the roller to fall in the depression of the strike, thereby holding the door closed
- The projection of the roller is easily adjusted using adjusting screws on the face of
- Maximum projection of the roller is <sup>3</sup>/<sub>8</sub>" allowing for variance in the door clearance
- Nylon roller standard
- Units packed with wood and machine screws to meet most field conditions
- RL30A model packed with ASA strike

### **Specifications**

| Material substrate | Made from forged brass          |
|--------------------|---------------------------------|
| Certifications     | Meets ANSI/BHMA A156.16, E19091 |

### **Dimensions**

| Body                           | Strike                         | Optional ASA strike   |
|--------------------------------|--------------------------------|---|
| 1 1/8" W x 2 1/4" H x 2 1/4" D | 1 1/8" W x 2 3/4" H x 3/32" T, | 1 <sup>1</sup> / <sub>4</sub> " W x 4 <sup>7</sup> / <sub>8</sub> " H x <sup>3</sup> / <sub>32</sub> " T, |
|                                | lip to center - 1 1/4"         | lip to center - 1 1/4"  |

### **Available accessories**

- Strike ASA
- Security mounting screws
- Silencers

## RL32/RL32A

### Roller latch

- Recommended light duty cabinet and closet applications
- Actuation is simple, closing of the door causes the roller to fall in the depression of the strike, thereby holding the door closed
- The projection of the roller is easily adjusted by turning knurled knob on back of latch
- Maximum projection of the roller is 1/2" allowing for variance in the door clearance
- Fits heavy-duty cylindrical lock cutout
- Nylon roller standard
- Non-handed
- Units packed with wood screws
- RL32A model packed with ASA strike

## **Specifications**

| <u> </u>           |                                 |
|--------------------|---------------------------------|
| Material substrate | Made from brass                 |
| Certifications     | Meets ANSI/BHMA A156.16, E19091 |

#### **Dimensions**

| Body                           | Strike  | Optional ASA strike            |
|--------------------------------|---|--------------------------------|
| 1 1/8" W x 2 1/4" H x 2 1/4" D | $1^{1}/8^{11}$ W x $2^{3}/4^{11}$ H x $^{3}/_{32}$ T, | 1 1/4" W x 4 7/8" H x 3/32" T, |
|                                | lip to center - 1 1/4"                                | lip to center - 1 1/4"         |

### Available accessories

Strike - ASA

### RL30/30A and RL32/32A Finishes

| ВНМА     | Description       | Substrate | Finish   |  |  |  |
|----------|-------------------|-----------|----------|--|--|--|
| 605      | Bright Brass      | Brass     | US3      |  |  |  |
| 606      | Satin Brass       | Brass     | US4      |  |  |  |
| 612      | Satin Bronze      | Brass     | US10     |  |  |  |
| 613      | Oil Rubbed Bronze | Brass     | US10B    |  |  |  |
| 619      | Satin Nickel      | Brass     | US15     |  |  |  |
| 622      | Matte Black       | Brass     | BLK      |  |  |  |
| 625      | Bright Chrome     | Brass     | US26     |  |  |  |
| 626      | Satin Chrome      | Brass     | US26D    |  |  |  |
| 643e/716 | Aged Bronze       | Brass     | 643e/716 |  |  |  |

For other colors, consult factory,







