Latches, catches and bolts
Roller latches

RL36/RL36A

Roller latch

- Recommended light duty cabinet and closet applications
- Actuation is simple, closing of the door causes the roller to fall in the depression of the strike, thereby holding the door closed
- The projection of the roller is easily adjusted by turning slotted screw on back of latch
- Maximum projection of the roller is 5/16" allowing for variance in the door clearance
- Fits cylindrical lock cutout
- Nylon roller
- Non-handed
- Units packed with wood screws
- RL36A model packed with ASA strike

Specifications

Material substrate	Made from stainless steel
Certifications	Meets ANSI/BHMA A156.16, E57082

Dimensions

Body	Strike	Optional ASA strike
1" W x 2 1/4" H x 2" D	$1^{1}/_{8}$ " W x $2^{3}/_{4}$ " H x $^{3}/_{32}$ " T,	1 1/4" W x 4 7/8" H x 3/32" T,
	lip to center - 1 1/4"	lip to center - 11/4"

Finish

внма	Description	Substrate	Finish	
630	Satin Stainless	Stainless steel	US32D	

For other colors, consult factory.

Available accessories

Strike - ASA

RL38

Roller latch

- Rim style roller latch
- Actuation is simple, closing of the door causes the roller to fall in the depression of the strike, thereby holding the door closed
- The projection of the roller is easily adjusted by turning slotted screw
- Maximum projection of the roller is ³/₈" allowing for variance in the door clearance
- Nylon roller
- Non-handed
- Units packed with wood screws

Specifications

Material substrate	Made from stainless steel
Certifications	Meets ANSI/BHMA A156.16, L27092

Dimensions

Body	Strike
1 ³ / ₈ " W x 2" H x ⁷ / ₈ " D	1" W x 2 ½8" H x 3/8" D

Finish

ВНМА	Description	Substrate	Finish
630	Satin Stainless	Stainless steel	US32D

For other colors, consult factory.







