

Combination Push/Pull Latch and Mortise Lock

Mortise Lock Option

The HL6 Push/Pull Latch is available with a Schlage® L series heavy-duty mortise lock included. Mortise lock combination models are furnished in 2-3/4" backset.

Five Mounting Positions:

- Increased versatility
- Mount in five positions
 - Handles down
 - Handles up
 - One handle up, one handle down (either push or pull)
 - Handles point away from latch
- Suits a wide range of applications

Cylinder Operation:

Where cylinders are required, Glynn Johnson will supply locks less cylinders. An 1-1/8" cylinder with a cloverleaf cam is required. Handle on cylinder side must be mounted in down position, if vertical mounting is used.

Thumbturn Operation:

Where thumbturn operations are required, the handle must be mounted in horizontal position. Standard thumbturn is provided.

Mortise Lock Retrofit Kit:

Kits are available to retrofit existing installations and they include all necessary components. 9000RK is specified for the lock function. If Schlage mortise locks are already installed, the set can be easily converted to Push/Pull operation with minor modifications to door.

Mortise Lock Functions Available

For a full list of standard and special lock functions available see pages 10 and 11.

Six Options:

- B—Brass Base Material for US26 and US260 Finishes
- E—Engraved Handles – “PUSH” and “PULL”
- EN—Entrance Only Latch
- EO—Exit Only Latch
- L—Lead Lined
- SOC—Pin-in-Socket Security Screws

Finishes:

US3, US4, US10, US10B, US26, US26D, US32D

Unmatched Convenience:

- Non-Handed
- Variable mounting positions
- UL listed for all labeled metal or wood doors

Application Information

The unit combines the features and convenience of the HL6 Push/Pull operation with the durability of the heavy-duty mortise lock. The sleek design has a short throw angle, allowing the door to be opened with an easy push or pull action, even when hands are not free. The mortise lock offers many lock functions, see page 10 and 11 for the specific functions available. The only handle orientation not available would be handles pointing towards the latch edge of the door.

Options

Suffix B (Brass Base-Material)

The option of using brass handles and covers instead of the standard zinc for the US26 and US26D finishes.

Suffix E (Engraved Handles)

Adds engraving to the handles “push” and “pull”. See page 12 for engraving guide. Engraved handles are not recommended for humid applications.

Suffix EN (Entrance Only)

This Entrance Only latch is appropriate for doors where only one side is used for entry. Order HL6EN for applications where no exit is required.

Suffix EO (Exit Only)

This Exit Only latch is appropriate for doors where only one side is used for exit. Order HL6EO for applications where the security of no entry is required.

Suffix L (Lead Lining)

The lead lining kit provides lead components to cover cut-outs made in lead lined doors.

Suffix SOC (Pin-in-Socket Security Screws)

The option of having pin-in-socket security screws instead of standard screws. Pin-in-Socket screws are provided for the strike, latch bolt and covers.



How to Order

HL6 - - - -

Options:

- B** Brass Base Material on US26 and US26D
- E** (1, 2, 3, 4, 5 or 6)— Engraved handles
- EN** Entrance Only
- EO** Exit Only
- L** Lead Lined
- SOC** Pin-in-Socket Security Screws

Lock Function: See pages 10 and 11
9000RK Retrofit Kit

Finishes:

US3, US4, US10, US10B, US26, US26D, US32D

Door Thickness:

Blank 1-3/4" door, specify other thickness

Mortise Lock Functions Available

Standard Lock Functions

Lock Number – ANSI Functions – Description

9010 – F01 – Passage Latch

Latchbolt retracted by handle from either side at all times.

9040 – F22 – Bath/Bedroom Privacy Lock

Latchbolt retracted by handle from either side unless outside is locked by inside thumbturn. Activating inside handle or closing door unlocks outside handle. To unlock from outside, remove emergency button, insert emergency turn in access hole and rotate.

9050 – F04 – Office/Inner Entry Lock

Latchbolt retracted by handle from either side unless outside is made inoperative by key outside or by turning inside thumbturn. When outside is locked, latchbolt is retracted by key outside or by handle inside. Outside handle remains locked until thumbturn is turned to the unlocked position or outside key is unlocked. Auxiliary latch deadlocks latchbolt when door is closed.

9060 – F09 – Apartment Lock

Latchbolt retracted by handle from either side unless outside is locked by key from inside. When locked, latchbolt retracted by key outside or handle inside. Auxiliary latch deadlocks when door is closed.

9070 – F05 – Classroom Lock

Latchbolt retracted by handle from either side unless outside is locked by key. Unlocked from outside by key. Inside handle always free for immediate exit. Auxiliary latch deadlocks latchbolt when door is closed.

9080 – F07 – Storeroom Lock

Latchbolt retracted by key outside or by handle inside. Outside handle always inoperative. Auxiliary latch deadlocks latchbolt when door is closed.

9080EL – Electrically Locked (Fail Safe)

Outside handle continuously locked by 24V AC or DC. Latch bolt retracted by key outside or handle inside. Switch or power failure allows outside handle to retract latchbolt. Auxiliary latch deadlocks latchbolt when door is closed. Inside handle always free for immediate exit.

9080EU – Electrically Unlocked (Fail Secure)

Outside handle unlocked by 24V AC or DC. Latchbolt retracted by key outside or handle inside. Auxiliary latch deadlocks latchbolt when door is closed. Inside handle always free for immediate exit.

9082 – Institution Lock

Latchbolt retracted by key from either side. Handle on both sides always inoperative. Auxiliary latch deadlocks latchbolt when door is closed.

9453 – F20 – Entrance Lock

Latchbolt retracted by handle from either side unless outside is locked by 20 rotation of thumbturn. When locked, key outside or handle inside retracts deadbolt and latchbolt simultaneously. Outside handle remains locked until thumbturn is restored to vertical position. Throwing deadbolt automatically locks outside handle. Auxiliary latch deadlocks latchbolt when door is closed.

9456 – F13 – Corridor Lock

Latchbolt retracted by handle from either side. Deadbolt thrown or retracted by key outside or inside thumbturn. Throwing deadbolt locks outside handle. Activating inside handle simultaneously retracts deadbolt and latchbolt, and unlocks outside handle.

9465 – Closet/Storeroom Lock

Latchbolt retracted by handle from either side. Deadbolt extended or retracted by key outside.

9466 – F14 – Store/Utility Room Lock

Latchbolt retracted by handle from either side. Deadbolt thrown or retracted by key from either side.

9473 – F21 – Dormitory/Bedroom Lock

Latchbolt retracted by handle from either side. Deadbolt thrown or retracted by key outside or thumbturn inside.

9485 – Hotel Lock

Latchbolt retracted by key outside or by handle inside. Outside handle always fixed. Deadbolt thrown or retracted by inside thumbturn. When deadbolt is thrown, all keys become inoperative except emergency or display keys. Activating handle retracts both deadbolt and latchbolt simultaneously. Auxiliary latch deadlocks latchbolt when door is closed.