

Meets ANSI/BHMA A156.9 B22201 and A156.14 D2781

221 Flush Pull

- Ideal for use on sliding doors.
- Built-in prong design eliminates the need for screws or brads and facilitates installation.
- Packed with two escutcheon pins for added holding power.
- · Made from wrought brass.

Dimensions

Inside Cup Diameter: 2-1/8" Overall Diameter: 2-7/16" Depth: 7/16"

Finishes brass

Ives Number	В3	B4	B5	B10	B10B	B15	B15A*	B26	B26D	B716
BHMA	605	606	609	612	613	619	620	625	626	

^{*} only available in Slim-Pak of 25

222 Flush Pull

- Low profile makes this pull ideal for louvered, bi-folding or wardrobe doors.
- · Reverse tapered grip provide for ease of pulling.
- · Made from cast brass.

Dimensions

3-1/8" High x 1-5/8" Wide x 7/16" Deep

Finishes brass

Ives Number	В3	B4	B5	B10	B10B	B15	B26	B26D
BHMA	605	606	609	612	613	619	625	626

Meets ANSI/BHMA A156.9 B12201 and A156.14 D1781.

Meets ANSI/BHMA A156.9 B22201 and A156.14 D2781.

223 Flush Pull

- Low profile makes this pull ideal for louvered, bi-folding or wardrobe doors.
- Made from wrought brass

Dimensions

3-9/16" High x 1-5/16" Wide x 1/2" Deep

Finishes brass

Ives Number	B3	B4	B10	B10B	B15	B26	B26D	
ВНМА	605	606	612	613	619	625	626	