



Meets ANSI/BHMA A156.16

481 Chain Door Guard

- Permits the door to be slightly opened to allow viewing.
- Narrow chain holder maintains chain in stationary position when door guard is not in use, eliminating marring of door and frame caused by dangling chain.
- Welded twist link steel chain finished to match door plate and chain holder.
- Made from wrought brass or burnished wrought steel.
- Packed with sheet metal screws.

Dimensions

Door Plate: 3-3/8" Long x 1-7/16" Wide
 Chain Holder: 1-10/16" High x 3/4" Wide
 Chain Length: 4-3/4"

Finishes brass

Ives Number	B3	B26D
BHMA	605	626

Finishes steel

Ives Number	F3	F4	F5	F10	F15	F26	F26D	F716
BHMA	632	633	638	639	646	651	652	



Meets ANSI/BHMA A156.16

482 Solid Bar Door Guard

- For use on doors that are flush with frames.
- The solid bar, interlocking with the ball on the strike plate, permits the door to be slightly opened to allow viewing.
- The hinged bar allows the door guard to be positioned 180° away from the door when not in use.
- Edge guard only, furnished with cast brass door guards, minimizes the chance for marring the door or frame.
- Strike plate is designed to prevent the solid bar from marring the inside of the door when in use.
- Made from cast brass or cast aluminum.
- Packed with sheet metal screws.
- Shims available in US26D (626) only, 1/8" or 3/8". Only fits 482B.

482B Cast Brass Dimensions

Strike Plate: 2-5/8" High x 1-1/32" Wide
 Holder: 1-3/4" High x 1-1/16" Wide
 Arm Length: 4-3/4"
 Edge Guard: 1-1/8" High x 1-1/32" Wide

482A Cast Aluminum Dimensions

Strike Plate: 2-1/2" High x 7/8" Wide
 Holder: 2-1/2" High x 15/16" Wide
 Arm Length: 3-13/16"

Finishes brass

Ives Number	B3	B4	B10	B10B	B15	B26	B26D
BHMA	605	606	612	613	619	625	626

Finishes aluminum

Ives Number	A3	A5	A26	A26D
BHMA	666		672	702