



Meets ANSI A156.3 Type 27.
 UL Listed 3 Hour Fire Doors 8'0" x 10'0"

FB51P Top and Bottom Bolts (Pair)

- Constant Latching—inactive door remains latched until the active door is opened, releasing the automatic bottom bolt and then the top bolt can be manually released. Inactive door will relatch automatically when closed.
- Low Actuation Forces.
- Fits standard ANSI A115.4 Door and Frame Preparations.
- Non-handed.
- 3/4" bolt throw with a 7/8" vertical adjustment.
- 3/4" backset
- Standard Rod Length is 12", which is measured from the center of the flush bolt body to the bolt tip. Optional rod lengths available for top bolt only on non-fire rated openings—18", 24", 36" and 48".

DP1 or DP2 optional dust proof strike available, see page C11.

FB51T Top Bolt Only

FB52 Top Bolt with Auxiliary Fire Latch

- FB52 Model with Auxiliary Fire Latch eliminates the bottom bolt and is UL Listed for Fire Doors.

FB53 Top Bolt with Auxiliary Fire Latch & Retrofit Plate

- FB53 Model with Auxiliary Fire Latch eliminates the bottom bolt and includes a retrofit plate to cover existing bottom bolt prep. UL Listed for Fire Doors.



Meets ANSI A156.3 Type 27.
 UL Listed 3 Hour Fire Doors 8'0" x 10'0"

Dimensions

- Body Size: 1" Wide x 6-3/4" Long x 2" Deep
- Guide Size: 1" Wide x 1-27/32" Long x 11/16" High x 3/32" Thick
- Strike Size: 15/16" Wide x 2-1/4" Long x 1/16" Thick
- Rub Plate Size: 1-1/4" Wide x 1-11/16" Long x 3/64" Thick
- Auxiliary Fire Latch Size: 1" Wide x 1-3/4" Long x 3-1/4" Deep
- Retrofit Plate Size: 1" Wide x 6-3/4" Long x 3/32" Thick

Finishes

| Ives Number | US3 | US4 | US10 | US10B | US32 | US32D |
|-------------|-----|-----|------|-------|------|-------|
| BHMA | 605 | 606 | 612 | 613 | 629 | 630 |