



**FS18S  
FS18L Floor Stops**

- Security Door Stops designed for use in high vandalism areas.
- Molded from black flame resistant, resilient material around a heavy-duty stud.
- Once grouted in concrete, leaves no exposed fasteners to be tampered with or removed.
- Ideal for jail or security cell areas where floor mounted stops are required.
- FS18L also ideal for concrete wall applications.

**Dimensions**

FS18S Height: 1-1/2"                      FS18L Height: 3-1/2"  
 FS18S Diameter: 2"                      FS18L Diameter: 2"  
 FS18S Stud Length: 2-1/2"              FS18L Stud Length: 2-1/2"

**FS434 Floor Stop**

- Burnished wrought steel.
- For undercut doors up to 1-1/2".
- Packed with screws and plastic anchors.
- Replaceable soft, resilient gray rubber.



**Dimensions**

Overall Height: 2-5/8"  
 Base Size: 1-1/2" W x 2-3/4" L

**Finishes**

Ives Number	USC
BHMA	604

**430 Floor Door Stop**

- Burnished wrought steel.
- For undercut doors up to 1-1/2".
- Packed with screws and plastic anchors.
- Replaceable soft, resilient gray rubber.



**Dimensions**

Overall Height: 1-5/16"  
 Base Diameter: 1-1/4"

**Finishes brass**

Ives Number	B3	B4	B5	B10B	B15	B26	B26D
BHMA	605	606	609	613	619	625	626

**Finishes aluminum**

Ives Number	A3*	A5	A14	A92
BHMA	666		669	673

\* only available in Slim-Pak of 25

A Hinges & Pivots  
 B Pulls & Plates  
 C Flush Bolts & Coordinators  
 D Latches, Catches & Bolts  
**E5 Stops**  
 F Exterior Hardware  
 G Miscellaneous Hardware