



5BB1 5 Knuckle, ball bearing full mortise hinge

- Recommended for medium weight doors (<150 lbs)
- Recommended for medium frequency usage (<400 cycles per day)
- Made with two ball bearing assemblies
- Recommended for use with a door closer
- Packed with fasteners for hollow metal and wood doors
 - 12-24 x 1/2 UFPHMS, 12 x 1 1/4 FPHWS
 - 10-24 x 1/2 UFPHMS, 10 x 1 FPHWS (3.5x3.5 hinge size only)

Certifications

- Certified to ANSI/BHMA A156.1 for performance standards
- Meets ANSI/BHMA 156.7 for template hinge dimensions
- UL Classified for windstorm rated assemblies - R37965
- UL Listed, 3 hour fire doors

Material substrate

- Made from brass, 1040 steel, or 304 series stainless steel

Dimensions

Height x Width	Size (mm)	Gauge
3.5 x 3.5	89 x 89	0.123
4 x 4	102 x 102	0.130
4.5 x 4	114 x 102	0.134
4.5 x 4.5	114 x 114	0.134
5 x 4.5	127 x 114	0.146
5 x 5	127 x 127	0.146

Refer to General Hinge Information page to determine proper hinge for application

5BB1 Finishes

BHMA	Description	Substrate	Finish
600	Primer paint	Steel	USP
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
610	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
614	Oxidized bronze	Brass	US10A
616	Blackened bronze	Brass	US11
619	Satin nickel	Brass	US15
622	Matte black	Brass	B-BLK
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D
643e/716	Aged bronze	Brass	B-643e/716
629	Bright stainless	Stainless steel	US32
630	Satin stainless	Stainless steel	US32D
631	Matte black	Steel	F-BLK
632	Bright brass	Steel	US3
633	Satin brass	Steel	US4
639	Satin bronze	Steel	US10
640	Oil rubbed bronze	Steel	US10B
641	Oxidized bronze	Steel	US10A
643	Blackened bronze	Steel	US11
646	Satin nickel	Steel	US15
651	Bright chrome	Steel	US26
652	Satin chrome	Steel	US26D
643e/716	Aged bronze	Steel	F-643e/716

For other colors, consult factory.

Options


- NRP Non-removable pin
- HT Hospital tip
- SH Security stud - comes standard with NRP
- RC-1/4, RC-5/8... Rounded corners
- SEC Security fasteners - pin-in-socket
- TW4 Four wire
- TW4M Four wire with monitor
- TW8 Eight wire
- TW8M Eight wire with monitor
- MON Monitor (not available on 3.5X3.5)

General information - electrification options

Electrical through-wire (TW4 and TW8)

Provides electric power transfer from the frame to the door in order to supply power to an electrified mortise or cylindrical locks, exit devices with electric latch retraction, and/or electric strikes (pairs of doors). Through-wire is rated 50 volts AC/DC at 3.5 amp continuous and 16 amp pulse. Maximum pulse 400 milliseconds. Ives through-wire hinges are fully compatible with 4 wire (TW4) and 8 wire (TW8) installations. Available CON option comes with the Allegion Connect 8-pin Connector which makes it easy to connect to other electrical consumption devices.

- UL634 Listed
- Not available 3PB1, 3SP1, and 5PB1 models
- Not available on 3.5 x 3.5 size hinges
- Not available with security stud (SH) option
- Packaged one hinge per box with standard wood and machine screws
- Hinge is NRP as a standard
- High quality brass ferrules and plastic tubing protect the wires
- Through-wire hinges cycle tested to ensure durability
- Special wire gauge, number, and color configurations available, contact factory



Electrical Monitor (MON, TW4M, TW8M)

Provides door position monitoring. Monitor is rated 30 volts AC/DC at 0.5 amp. Fully compatible with through-wire hinges with 4 wire (TW4M) and 8 wire (TW8M) installations. Available CON option comes with the Allegion Connect 8-pin Connector which makes it easy to connect to other electrical consumption devices.

- UL634 Listed
- Not available 3PB1, 3SP1, and 5PB1 models
- Not available on 3.5 x 3.5 and 4X4 size hinges
- Not available with security stud (SH) option
- Packaged one hinge per box with standard wood and machine screws
- Hinge is NRP as a standard
- High quality brass ferrules and plastic tubing protect the wires
- Through-wire hinges cycle tested to ensure durability
- Special wire gauge, number, and color configurations available, contact factory