

Hinges and pivots

Architectural hinges

5BBIWT

5 Knuckle, ball bearing, wide throw full mortise hinge

- Recommended for medium weight doors (<150 lbs)
- Recommended for medium frequency usage (<400 cycles per day)
- Made with two ball bearing assemblies
- Recommended for use with a door closer
- Packed with fasteners for hollow metal and wood doors
 - 12-24 x 1/2 UFPHMS, 12 x 1 1/4 FPHWS



Specifications

Material substrate	1040 steel
Certifications	<ul style="list-style-type: none"> ▪ Certified ANSI/BHMA A156.1 for performance standards ▪ Meets ANSI/BHMA 156.7 for template hinge dimensions

Dimensions

Height x Width	Size (mm)	Gauge
4.5 x 5	114 x 127	0.134
4.5 x 6	114 x 152	0.134
5 x 6	127 x 152	0.146
5 x 7	127 x 178	0.146
5 x 8	127 x 203	0.146

Refer to General Hinge Information page to determine proper hinge for application

Options

NRP	Non-removable pin	TW4	Four wire
HT	Hospital tip	TW4M	Four wire with monitor
SH	Security stud - comes standard with NRP	TW8	Eight wire
RC-1/4, RC-5/8	Rounded corners	TW8M	Eight wire with monitor
SEC	Security fasteners - pin-in-socket (for hollow metal doors and frames only)	MON	Monitor

All electrified wide throws are an engineered special.

Finishes

BHMA	Description	Substrate	Finish
600	Primer Paint	Steel	USP
631	Matte Black	Steel	F-BLK
632	Bright Brass	Steel	US3
633	Satin Brass	Steel	US4
639	Satin Bronze	Steel	US10
640	Oil Rubbed Bronze	Steel	US10B
641	Oxidized Bronze	Steel	US10A
646	Satin Nickel	Steel	US15
651	Bright Chrome	Steel	US26
652	Satin Chrome	Steel	US26D
643e/716	Aged Bronze	Steel	F-643e/716
695	Dark Bronze Painted	Steel	F-695/US10BE

For other colors, consult factory.