

Hinges and pivots

Intermediate pivots

7212-7212V-7222 INT

3/4" Offset intermediate pivot

NFPA 80, Section 3-3.8 requires intermediate pivot on some fire door applications, consult product support. Use for door heights over 7'0" and one every 2'6" as needed.

- This intermediate pivot is used with 7212, 7212V, and 7222 offset pivots
- Use for door weight over the pivot set limit.
Use one additional pivot for every additional 100 pounds.
- Recommended for use with 1 3/4" minimum door thickness, with 1/8" bevel in 2"
- Handed LH or RH

Specifications

Material substrate	Made from cast brass
Certifications	<ul style="list-style-type: none"> ▪ Meets ANSI/BHMA A156.4 C07382 ▪ UL10C Listed (3 hour)

7212-7212V-7222 INT Finishes

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
612	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
619	Satin nickel	Brass	US15
622	Matte black	Brass	BLK
625	Bright chrome	Brass	625
626	Satin chrome	Brass	626
-	Aged bronze	Brass	643e/716
689	Aluminum painted	Brass	SP28
691	Bronze painted	Brass	SP10
695	Dark bronze painted	Brass	SP313/US10BE
706	Brass painted	Brass	SP4

For other colors, consult factory.

