

Hinges and pivots

Offset pivots

7244F

1 1/2" Offset pivot, 400lb with top header mount
and bottom base mount (fire rated)

- Maximum door load 400 pounds
- Recommended for use with 1 3/4" minimum door thickness, with 1/8" bevel in 2"
- Vertical adjustment range 3/16", with positive locking
- Non-handed
- 7244F Set (7244F Top and 7244F Btm)
- 7244F Top (7244F-7245F Top), header mount
- 7244F Btm (7244F Btm), base mount

Specifications

Material substrate	Made from 304 series stainless steel
Certifications	<ul style="list-style-type: none"> ▪ Meets ANSI/BHMA A156.4 C07162 ▪ UL10C Listed (3 hour)

Available accessories

7244F INT (7244F-7245F) Intermediate pivot (handed) as needed; for additional electrical wiring applications, consult product support

See general information for specifics on how many intermediate pivots are recommended.

7244F Finishes

BHMA	Description	Substrate	Finish
629	Bright stainless	Stainless steel	US32
630	Satin stainless	Stainless steel	US32D
631	Matte black	Stainless steel	BLK
632	Bright brass	Stainless steel	US3
639	Satin bronze	Stainless steel	US10
–	Aged bronze	Stainless steel	643e/716
689	Aluminum painted	Stainless steel	SP28
691	Bronze painted	Stainless steel	SP10
695	Dark bronze painted	Stainless steel	SP313/US10BE
706	Brass painted	Stainless steel	SP4

For other colors, consult factory.

