

8102HD Solid door pull - 3/4" round

Available Sizes: 6", 8", 10"

Certifications

Meets ANSI A156.06

Mounting

- Heavy duty mounting hardware exceeds industry standards
- 5/16-18 mounting hardware
- Specify door thickness. Standard mounting hardware for door thickness of 1-1/2" to 1-3/4" unless otherwise specified. Optional package available for 2" and 2-1/4" thick doors.
- Comes standard with thru-bolt screws and decorative washers.
- Optional mounting hardware available (see general information section for details) F, G, I, J, L
- *Mounting hardware for other door thicknesses are available as engineering special, consult customer service.*

Product number	Projection "A"	Clearance	Center to center "B"	Overall length "C"
8102HD-6	2-1/4"	1-1/2"	6"	6-3/4"
8102HD-8	2-1/4"	1-1/2"	8"	8-3/4"
8102HD-10	2-1/4"	1-1/2"	10"	10-3/4"

Finishes

- Available in Aluminum, Brass, and Stainless Steel substrates. See general information section for specific BHMA finish code, finish description, US finish code, and substrate information.
- Standard finishes available; 605, 606, 612, 613, 619, 625, 626, 626-AM, 628, 629, 630, 630-AM, 643e/716, BLK
- *Custom finishes are available as engineering special, consult customer service.*

Additional information

- Specify PR when ordering a set of pulls for back to back mounting
- For one back to back machined pull, specify Jsgl
- *Custom lengths are available as engineering special, consult customer service.*

A
Hinges & pivots

B11
Pulls & plates

C
Flush bolts & coordinators

D
Latches, catches & bolts

E
Stops


F
Exterior hardware

G
Miscellaneous hardware

Mounting sizes


- All mounting hardware is for standard 1-3/4" door.
- Optional mounting hardware for 2" and 2-1/4" doors for many pulls. See pull detail for availability.
- Other mounting hardware sizes available as engineering special. Consult Customer Service.

Thru-bolt mounts




Standard mount

- Standard thru-bolt mount with countersunk washers
 - Hollow metal and wood door applications
- (2) Flat head mounting screws, plated to match
- (2) Countersunk washers, plated to match




F Mount - Countersunk holes

- Used with countersunk holes in doors
 - Wood door applications
- (2) Flat head mounting screws, plated to match




O Mount - Decorative

- Decorative thru-bolt mount
 - Hollow metal and wood door applications
- (2) Decorative mounting bolts - machine screw, plated to match



Q Mount - Decorative, glass doors

- Decorative thru-bolt mount
 - Glass door applications
- (2) Decorative mounting bolts - machine screw, plated to match
- (2) Metal and vinyl washers



X Mount - Security

- Security thru-bolt mount with countersunk washers
 - Hollow metal and wood door applications
- (2) Flat head security pin in socket mounting screws, plated to match
- (2) Countersunk washers, plated to match

A
Hinges & pivots

B5
Pulls & plates

C
Flush bolts & coordinators

D
Latches, catches & bolts

E
Stops


F
Exterior hardware

G
Miscellaneous hardware

Mounting sizes


- All mounting hardware is for standard 1-3/4" door.
- Optional mounting hardware for 2" and 2-1/4" doors for many pulls. See pull detail for availability.
- Other mounting hardware sizes available as engineering special. Consult Customer Service.

Concealed mounts




A Mount - Aluminum doors

- Concealed mount
 - Aluminum door applications
- (2) Mounting bolts - machine screw
- (2) Set screws
- Designed to be used with rivet nuts. Not supplied.




G Mount - Pull plate

- Concealed mount with pull plate
 - Hollow metal and wood door applications
- Pull mounts directly onto plate, Plate is attached to door
- (2) Flat head mounting screws



I Mount - Wood doors

- Concealed mount
 - Wood door applications
- (2) Mounting bolts - machine screw
- (2) Set screws




L Mount - Hollow metal doors

- Concealed mount
 - Hollow metal door applications
- (2) Mounting bolts - machine screw
- (2) Set screws

Mounting sizes


- All mounting hardware is for standard 1-3/4" door.
- Optional mounting hardware for 2" and 2-1/4" doors for many pulls. See pull detail for availability.
- Other mounting hardware sizes available as engineering special. Consult Customer Service.

Back to back mounts




J Mount - 8102 Pull only

- Back to back mounting - 5/16-18 hardware
 - Hollow metal and wood door applications
- (2) Mounting bolts - machine screw
- (2) Set screws




K Mount - 8121 Pull only

- Back to back mounting - 8-32 hardware
 - Hollow metal and wood door applications
- (8) Machine screws
- (4) Mounting sleeves



N Mount

- Back to back mounting - 3/8-16 hardware
 - Hollow metal and wood door applications
- (2) Mounting bolts - machine screw
- (2) Set screws



P Mount - Glass doors

- Back to back mounting - 3/8-16 hardware
 - Glass door applications
- (2) Mounting bolts - machine screw
- (2) Set screws
- (2) Metal and vinyl washers

Hinges & pivots
A

Pulls & plates
B7

Flush bolts & coordinators
C

Latches, catches & bolts
D

Stops
E

Exterior hardware
F

Miscellaneous hardware
G