

## Latches, catches and bolts

### Ball catches

# CL21

#### Ball catch

- Four-way catch with hexagon stud
- Ideal for holding medium duty doors
- The strike slides between two stainless steel balls that are under spring tension; as the strike engages, the door is held tightly shut
- Strike can enter body from any direction
- Spring tension is easily adjusted to suit field conditions
- Body can be surface applied or mortised
- Units packed with wood screws

#### Specifications

Material substrate	Made from brass
Certifications	Meets ANSI/BHMA A156.9


#### Dimensions

Body	Strike
$\frac{3}{4}$ " W x 3" H x $\frac{3}{4}$ " D	$\frac{3}{4}$ " W hex x 1 $\frac{1}{2}$ " H

#### Finish

BHMA	Description	Substrate	Finish
604	Clear Zinc	Steel	F2C

For other colors, consult factory.



#### Available accessories

- Security pin screws

# CL21A

#### Ball catch

- Four-way catch with plate type strike
- Ideal for closet doors, access doors, hinged openings and numerous other applications
- The strike slides between two stainless steel balls that are under spring tension; As the strike engages, the door is held tightly shut
- Strike can enter body from any direction
- Spring tension is easily adjusted to suit field conditions
- Body can be surface applied or mortised
- Units packed with wood screws

#### Specifications

Material substrate	Made from brass
Certifications	Meets ANSI/BHMA A156.9, B13292

#### Dimensions

Body	Strike
$\frac{3}{4}$ " W x 3" H x $\frac{3}{4}$ " D	$\frac{7}{16}$ " W x 1 $\frac{3}{4}$ " H x $\frac{7}{8}$ " D



#### Available accessories

- Security pin screws

# CL22

#### Ball catch

- Three-way catch with plate type strike
- Ideal for smaller cabinet doors or panels
- The strike slides between two stainless steel balls that are under spring tension; as the strike engages, the door is held tightly shut
- Strike can enter body from either side or front
- Spring tension is easily adjusted to suit field conditions
- Body can be surface applied or mortised
- Units packed with wood screws

#### Specifications

Material substrate	Made from brass
Certifications	Meets ANSI/BHMA A156.9, B13292

#### Dimensions

Body	Strike
$\frac{3}{4}$ " W x 3" H x $\frac{3}{4}$ " D	$\frac{7}{16}$ " W x 1 $\frac{3}{4}$ " H x $\frac{7}{8}$ " D



#### Available accessories

- Security pin screws

#### CL21A and CL22 Finishes

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
612	Satin bronze	Brass	US10
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D

For other colors, consult factory.