



COR7G and COR9G Gravity coordinators

- When active door is open, coordinator prevents active door from closing until inactive door bypasses. Closing of inactive door causes strike plate on top of door to contact cam and lift arm, allowing active door to close. As inactive door continues closing, roller rides over strike plate on to door bracket, holding arm above active door.
- Non-handed.
- Gravity action arm and door bracket are adjustable on the job for ease of installation. Rubber roller provides quiet and efficient operation, and helps protect the astragal and doors from damage.
- Nylon roller on short arm glides smoothly over door bracket and strike, ensuring silent operation.

Certifications

- Meets ANSI A156.3 Type 21B
- UL Listed for fire doors

Mounting

- 8-32 X 1" FPHMS

Material substrate

- Forged brass

Sizes

- COR7G 7" projection
 - COR7G for use on pairs of doors with astragal on active door up to 4' or with astragal on inactive door up to 3'4" or with astragal on both doors up to 2'10"
- COR9G 9" projection
 - COR9G for use on pairs of doors with astragal on active over 4' or with astragal on inactive door over 3'4" or with astragal on both doors over 2'10"

Finishes

BHMA	Description	Substrate	US
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
612	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D

Custom finishes are available as engineering special, consult customer service.

Available accessory items

- Security pin screws
- Replacement mounting package
- Replacement roller and bolt package
- Replacement rubber roller and pin package
- Replacement rub plate package

Hinges & pivots

A

Pulls & plates

B

Flush bolts & coordinators

C23

Latches, catches & bolts

D

Stops

E

Exterior hardware

F

Miscellaneous hardware

G