

## Flush bolts, strikes and coordinators

### Coordinators, filler bars and mounting brackets

# COR7G/COR9G

## Gravity coordinators

- When active door is open, coordinator prevents active door from closing until inactive door bypasses
  - Closing of inactive door causes strike plate on top of door to contact cam and lift arm, allowing active door to close
  - As inactive door continues closing, roller rides over strike plate on to door bracket, holding arm above active door
- Non-handed
- Gravity action arm and door bracket are adjustable on the job for ease of installation (rubber roller provides quiet and efficient operation, and helps protect the astragal and doors from damage)
- Nylon roller on short arm glides smoothly over door bracket and strike, ensuring silent operation.

## Specifications

|                    |  |
|--------------------|--|
| Available sizes    | <ul style="list-style-type: none"> <li>COR7G 7" projection - for use on pairs of doors with astragal on active door up to 4' or with astragal on inactive door up to 3'4" or with astragal on both doors up to 2'10"</li> <li>COR9G 9" projection - for use on pairs of doors with astragal on active over 4' or with astragal on inactive door over 3'4" or with astragal on both doors over 2'10"</li> </ul> |
| Material substrate | Forged brass   |
| Mounting hardware  | 8-32 X 1" FPHMS  |
| Certifications     | <ul style="list-style-type: none"> <li>Meets ANSI/BHMA A156.3 Type 21B</li> <li>UL Listed for fire doors</li> </ul>  |

## Finishes

| BHMA | Description       | Substrate | Finish |
|------|-------------------|-----------|--------|
| 605  | Bright Brass      | Brass     | US3    |
| 606  | Satin Brass       | Brass     | US4    |
| 612  | Satin Bronze      | Brass     | US10   |
| 613  | Oil Rubbed Bronze | Brass     | US10B  |
| 625  | Bright Chrome     | Brass     | US26   |
| 626  | Satin Chrome      | Brass     | US26D  |

Custom finishes are available as engineering special, consult customer service.

## Available accessories

- Security pin screws
- Replacement mounting package
- Replacement roller and bolt package
- Replacement rubber roller and pin package
- Replacement rub plate package

# CBI

## Carry bar

- Used when it is possible for the inactive door to be opened before the active door
- Prevents damage to the doors and other hardware
- Nylon roller insures quiet and efficient operation
- Non-handed
- Standard through bolts for mounting

## Specifications

|                    |                                 |
|--------------------|---------------------------------|
| Material substrate | All-steel construction          |
| Certifications     | Meets ANSI/BHMA A156.3 Type 21A |

## Dimensions

| Door closed     | Door open       |
|-----------------|-----------------|
| 1 5/8" X 5 3/4" | 1 5/8" X 2 1/2" |

## Finishes

| BHMA | Description       | Substrate | Finish |
|------|-------------------|-----------|--------|
| 600  | Primed for paint  | Steel     | USP    |
| 632  | Bright Brass      | Steel     | US3    |
| 633  | Satin Brass       | Steel     | US4    |
| 639  | Satin Bronze      | Steel     | US10   |
| 640  | Dark Satin Bronze | Steel     | US10B  |
| 651  | Bright Chrome     | Steel     | US26   |
| 652  | Satin Chrome      | Steel     | US26D  |
| -    | Flat Black Coated | Steel     | BLK    |

Custom finishes are available as engineering special, consult customer service.

## Available accessories

- Security pin screws
- Replacement nylon roller and pin package

