

Flush bolts, strikes and coordinators

Dust proof strikes

DP1/DP2

Dust proof strike

- DP1 - round face plate
- DP2 - rectangular face plate
- Designed for use with the bottom bolt of all flush bolts
- Spring-loaded plunger returns to floor or threshold level anytime flush bolt is retracted, eliminating need to clean standard floor strikes
- Strike hole is $\frac{3}{4}$ " diameter and $1\frac{1}{8}$ " deep

Specifications

Mounting hardware 8-32 X 1" FPHMS

Dimensions

DP1 face plate (Diameter)	DP2 face plate (Width x Length x Thickness)	Body (Diameter x Depth)
$1\frac{7}{16}$ "	$1\frac{5}{8}$ " x $3\frac{1}{2}$ " x $\frac{1}{8}$ "	$1\frac{3}{16}$ " x $1\frac{7}{8}$ "

Finishes

BHMA	Description	Substrate	Finish
605	Bright Brass	Brass	US3
606	Satin Brass	Brass	US4
612	Satin Bronze	Brass	US10
613	Oil Rubbed Bronze	Brass	US10B
619*	Satin Nickel	Brass	US15
622*	Matte Black	Brass	BLK
625	Bright Chrome	Brass	US26
626	Satin Chrome	Brass	US26D
643e/716*	Aged Bronze	Brass	-

*Finishes only available with DP2

Custom finishes are available as engineering special, consult customer service.

Additional accessories

- Security pin screws



DP1



DP2