



FS1153 Plunger type door holder

- Provides a contemporary yet economical method of positive hold-open.
- Spring operated plunger activates with minimal pressure, releasing instantly with a light tap on the platform lever.
- Provides a 1-5/8" throw for all types of doors.
- Ribbed grey non-marring rubber shoe is securely fastened to unit with a screw and is easily replaced when worn.
- Packed with fasteners for wood applications

Certifications

- Meets ANSI/BHMA 156.16, L11401

Material substrate

- Made from cast brass

Available accessory items

- Replaceable grey non-marring rubber shoes

Dimensions

- Height: 5-1/2"
- Width: 2"
- Depth: 1-1/4"

Finishes - Aluminum

BHMA	Description	Substrate	Finish
628	Satin aluminum	Aluminum	US28

For other colors, consult factory.



FS1154 Plunger type door holder

- Plunger and internal parts are plated steel and provides a 1-1/4" throw for all types of doors.
- Plunger is easily activated with minimal pressure, releasing instantly with a light tap on the platform lever.
- Round non-marring rubber shoe is securely fastened with a screw in flanged cup to prevent movement or loss. When worn, shoes are easily replaced.
- Packed with fasteners for wood applications.

Certifications

- Meets ANSI/BHMA 156.16, L31401

Material substrate

- Made from cast aluminum

Dimensions

- Height: 6-1/4"
- Width: 1-1/2"
- Depth: 1-7/16"

Available accessory items

- Replaceable grey non-marring rubber shoes

Finishes

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
612	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D

For other colors, consult factory.

Hinges & pivots **A**

Pulls & plates **B**

Flush bolts & coordinators **C**

Latches, catches & bolts **D**

Stops **E17**

Exterior hardware **F**

Miscellaneous hardware **G**