



FS452 Kick down holder

- Units provide simple hold and release, activated with a touch of the foot
- Stainless steel spring
- Replaceable black non-marring rubber shoes have corrugated bottoms to provide secure grip. Rubber shoe is securely fastened with screw
- Shoes are easily replaced when worn
- Packed with fasteners for wood applications
- FS452-4 has a door-to-floor clearance of 2" or less
- FS452-5 has a door-to-floor clearance up to 3"

Certifications

- Meets ANSI/BHMA 156.16, L11383 for brass and L31383 for aluminum

Material substrate

- Made from cast brass or aluminum

Available accessory items

- Replaceable black non-marring rubber shoes

Dimensions

- FS452-4 Door-to-floor clearance: 2" or less
- FS452-5 Door-to-floor clearance: up to 3"
- FS452-4 Plate height: 2-1/8"
- FS452-5 Plate height: 2-1/8"
- FS452-4 Plate width: 1"
- FS452-5 Plate width: 1"

Finishes - Brass

BHMA	Description	Substrate	Finish
605	Bright brass	Brass	US3
606	Satin brass	Brass	US4
612	Satin bronze	Brass	US10
613	Oil rubbed bronze	Brass	US10B
619	Satin nickel	Brass	US15
622	Matte black	Brass	BLK
625	Bright chrome	Brass	US26
626	Satin chrome	Brass	US26D
---	Aged bronze	Brass	643e/716

Finishes - Aluminum

BHMA	Description	Substrate	Finish
628	Satin aluminum	Aluminum	US28

For other colors, consult factory. *Available in 4" only.

Hinges & pivots

A

Pulls & plates

B

Flush bolts & coordinators

C

Latches, catches & bolts

D

Stops

E15

Exterior hardware

F

Miscellaneous hardware

G