

Door stops, holders and silencers**Wall stops and holders**

FS544/FS555

Kick down holders

- FS544 - 4", FS555 - 5"
- Units provide an economical method to hold open doors
- Stainless steel spring
- Replaceable grey non-marring rubber shoes have corrugated bottoms to provide secure grip
 - Rubber shoe is securely fastened with screw
- Shoes are easily replaced when worn
- Packed with fasteners for wood applications
- FS544 for door-to-floor clearances of 2" or less
- FS555 for door-to-floor clearances up to 3"



FS544

Specifications

Material substrate	Made from cast iron
Certifications	<ul style="list-style-type: none"> ▪ FS544 Meets ANSI/BHMA 156.16, L11381 ▪ FS555 Meets ANSI/BHMA 156.16, L11391

Dimensions

Door to floor clearance	Plate height	Plate width
▪ FS544: 2" or less	▪ FS544: 2 1/4"	▪ FS544: 1 7/16"
▪ FS555: up to 3"	▪ FS555: 2 1/4"	▪ FS555: 1 7/16"

Finishes

BHMA	Description	Substrate	Finish
689	Aluminum Painted	Iron	SP28
691	Bronze Painted	Iron	SP10
695	Dark Bronze Painted	Iron	SP313
706	Brass Painted	Iron	SP4
–	Matte Black	Iron	BLK

For other colors, consult factory.

Available accessories

- Replaceable grey non-marring rubber shoes