

## Latches, catches and bolts

### Surface bolts

# SB1630/SB1640

#### Surface bolt

- Standard surface bolt has 1" throw for maximum security
- Ideal for all types of doors
- Fully concealed mounting prevents vandalism
- Units packed with wood and machine screws to meet most field conditions
- Comes end plug and end plug stud package
- Available in locking version, unit locks in both the up and down position
  - Locking bolts are furnished with 2 keys in 4 keying variations

#### Specifications

Material	▪ 1630 Series is constructed of heavy duty steel substrate
	▪ 1640 Series is constructed of brass
Certifications	▪ 1630 Meets ANSI/BHMA A156.16 L84161 and UL10C Listed (3 hour) fire doors up to 8'0"
	▪ 1640 Meets ANSI/BHMA A156.16 L24161

#### Dimensions

Body	Overall knob or lock housing projection	Top strike	Bottom strike
8" L x 7/8" W x 3/4" T	1 1/2"	1 1/4" W x 7/8" L x 15/16" D	3" L x 1" W x 1/8" T

#### Strike options

- **T** Top strike only
- **B** Bottom strike only
- **TB** Top and bottom strike\*
- **TL** Locking bolt with top strike only
- **BL** Locking bolt with bottom strike only
- **TBL** Locking bolt with top and bottom strike\*

#### Key code

- 1289 Standard key code
- 1360
- 1390
- 1395

\* Available on SB1630 Only

#### SB1630 Finishes

BHMA	Description	Substrate	Finish
603	Clear Zinc	Steel	US2G
640	Oil Rubbed Bronze	Steel	US10B
652	Satin Chrome	Steel	US26D

#### SB1640 Finishes

BHMA	Description	Substrate	Finish
605	Bright Brass	Brass	US3
613	Oil Rubbed Bronze	Brass	US10B
626	Satin Chrome	Brass	US26D

For other colors, consult factory.

#### Available accessories

- Security pin screw
- Through bolts available
- End plug and end plug stud package
- Cylinder package
- Replacement strike packages



Universal top strike



Flat bottom strike