



Meets ANSI/BHMA 156.16, L03011.

**SR64 Door Silencer**

- For use on metal frames featuring pneumatic design that, once installed, forms an air pocket to absorb shock and reduce noise of door closing.
- Tamper-proof once installed on the frame.
- Proper installation also eliminates door rattle and provides constant tension for door latches or locks.

Packed in bags of 100.  
 Grey Available in bulk pack of 2500.  
 Each bag has an installation tool included.

**Dimensions**

Diameter: 1/2"  
 Thickness: 1/8"

**Finishes**

GRY, TAN



Meets ANSI/BHMA 156.16, L03021

**SR65 Door Silencer**

- For use on wood frames, also feature pneumatic design to cushion shock and absorb noise.
- To prevent removal, a small brad should be driven into stop strip and through stem of silencer, as shown in the detail.

Packed in bags of 100.

**Dimensions**

Height: 3/4"  
 Diameter: 3/8"  
 Thickness: 1/8"

**Finishes**

GRY



**SR66 Door Silencer**

- Self Adhesive Rubber Silencers.
- Economical installation requires no drilling of frames.

Packed two sheets of 50 (100 minimum).

**Dimensions**

Diameter: 1/2"  
 Thickness: 1/8"

**Finishes**

BRN, GRY, WHT

A  
Hinges & Pivots

B  
Pulls & Plates

C  
Flush Bolts & Coordinators

D  
Latches, Catches & Bolts

E23  
Stops

F  
Exterior Hardware

G  
Miscellaneous Hardware