

Pulls, push bars and plates

Vandal resistant trim

VR810-NL / VR814-NL

Vandal resistant night latch trim, LHR and RHR options (models with and without black grip)

- VR810-NL (LHR or RHR) with black grip, VR814-NL (LHR or RHR) without black grip
- Closed pull design eliminates a hooking point to be able to forcibly pull a secured door open
- Ligature resistant design
- For use with Falcon XX-V
- Through bolts direct to the exit device
- Night latch operation (cylinder not furnished)
- 1⁵/₈" cylinder hole cut-out on door, located 1¹³/₁₆" above horizontal center line and centered between mounting studs on vertical center line
- Designed for use with 1¹/₄" cylinders
 - Other cylinders may require additional blocking rings, not supplied
- Supplied with protective cylinder collar
 - Collar spins to reduce damage from pipe wrench or other tool



VR810

VR814

Specifications

Available sizes	11 Gauge (0.120" thick)
Material substrate	304 Series stainless steel standard, exceeding industry standards for corrosion resistance. Recommended for external applications.
Mounting hardware	<ul style="list-style-type: none">▪ For door thickness 1³/₄"-2¹/₄"<ul style="list-style-type: none">- 10-24 X 1" and 10-24 X 1¹/₂" mounting screw size▪ Can be mounted directly to Falcon XX-V5 exit devices▪ Standard mounting - Welded studs fasten with pan head screws on opposite side of door▪ Optional through bolt mounting - bolt through face of trim into device for added security

Dimensions

Product number	Width	Height	Through bolt pattern (4 holes)	Clearance grip to door	Projection
VR810NL	5 ¹ / ₄ "	11"	1 ³ / ₄ " wide x 7 ³ / ₄ " high	1 ¹ / ₂ "	1 ⁷ / ₈ "

Finishes

BHMA	Description	Substrate	Finish
630	Satin Stainless	Stainless steel	US32D

Models are available with or without attractive black plastisol edge grip.

Custom finishes are available as engineering special, consult customer service.