

## Pulls, push bars and plates

### Vandal resistant trim

# VR810-NL-V/VR814-NL-V

## Vandal resistant night latch trim (models with and without black grip)

- VR810-NL-V with black grip, VR814-NL-V without black grip
- Closed pull design eliminates a hooking point to be able to forcibly pull a secured door open
- Ligature resistant design
- For use with Falcon 25-R or 25-V Series exit devices
- Through bolts direct to the exit device
- Night latch operation (cylinder not furnished)
- Non-handed, horizontal keyway
- 1 5/8" cylinder hole cut-out, on door, located at the horizontal center line 3/16" off of vertical centerline between mounting studs towards the strike edge of the door
- Designed for use with 1 1/4" cylinders
  - Other cylinders may require additional blocking rings, not supplied
- Supplied with protective cylinder collar
  - Collar spins to reduce damage from pipe wrench or other tool



VR810

VR814

### Specifications

Available sizes	11 Gauge (0.120" thick)
Material substrate	304 Series stainless steel standard, exceeding industry standards for corrosion resistance. Recommended for external applications.
Mounting hardware	<ul style="list-style-type: none"> <li>▪ For door thickness 1 3/4"-2 1/4"           <ul style="list-style-type: none"> <li>- 10-24 X 1" and 10-24 X 1 1/2" mounting screw size</li> </ul> </li> <li>▪ Can be mounted directly to Falcon 24-R or 25-V exit devices</li> <li>▪ Standard mounting - Welded studs fasten with pan head screws on opposite side of door</li> <li>▪ Optional through bolt mounting - bolt through face of trim into device for added security</li> </ul>

### Dimensions

Product number	Width	Height	Through bolt pattern (4 holes)	Clearance grip to door	Projection
VR810NL-V	5 1/4"	11"	1 3/4" wide x 7 3/4" high	1 1/2"	1 7/8"

### Finishes

BHMA	Description	Substrate	Finish
630	Satin Stainless	Stainless steel	US32D

Models are available with or without attractive black plastisol edge grip.

Custom finishes are available as engineering special, consult customer service.