

VR900/VR904

Vandal resistant mortise trim, LHR and RHR options (models with and without black grip)

- VR900 (LHR or RHR) with black grip, VR904 (LHR or RHR) without black grip
- Closed pull design eliminates a hooking point to be able to forcibly pull a secured door open
- Ligature resistant design
- For use with most mortise locks on out-swinging doors including Schlage L9000 Series with interior L or N escutcheon, and rose trim
- Built-in lock protector prevents tampering
- Handed design allows trim to be positioned to coordinate with the centerline of inside hardware
- 1 1/2" cylinder hole cut-out on door, located 2 7/32" above horizontal center line and 1/4" offset from vertical center line towards the hinge side of the door
- Designed for use with 1 1/4" cylinders
 - Other cylinders may require additional blocking rings, not supplied
- Supplied with protective cylinder collar
 - Collar spins to reduce damage from pipe wrench or other tool
- Additional cut-outs and locations are available as engineering special, consult customer service



Specifications

Available sizes	11 Gauge (0.120" thick)
Material substrate	304 Series stainless steel standard, exceeding industry standards for corrosion resistance. Recommended for external applications.
Mounting hardware	<ul style="list-style-type: none"> ▪ For door thickness 1 3/4"-2 1/4" <ul style="list-style-type: none"> – 1/4"-20 X 1 1/4" and 1/4"-20 X 1 3/4" mounting screws with countersunk washers ▪ Can be mounted directly to Schlage L9000 Series ▪ Standard mounting - Welded studs fasten with pan head screws on opposite side of door ▪ Optional through bolt mounting - bolt through face of trim into device for added security

Dimensions

Width	Height	Through bolt pattern (4 holes)	Clearance grip to door	Projection
7 1/4"	11"	2" wide x 10" high	1 1/2"	1 7/8"

Finishes

BHMA	Description	Substrate	Finish
630	Satin Stainless	Stainless steel	US32D

Models are available with or without attractive black plastisol edge grip.

Custom finishes are available as engineering special, consult customer service.