

Pulls, push bars and plates

Vandal resistant trim

VR900LLP/VR904LLP

Vandal resistant mortise trim, less lock protector, LH and RH options (models with and without black grip)

- VR900LLP with black grip, VR904LLP without black grip
- Closed pull design eliminates a hooking point to be able to forcibly pull a secured door open
- Ligature resistant design
- For use with most mortise locks on in-swinging doors including Schlage L9000 Series with interior L or N escutcheon, and rose trim
- Handed design allows trim to be positioned to coordinate with the centerline of inside hardware
- 1 1/2" cylinder hole cut-out on door, located 2 7/32" above horizontal center line
- Designed for use with 1 1/4" cylinders
 - Other cylinders may require additional blocking rings, not supplied
- Supplied with protective cylinder collar
 - Collar spins to reduce damage from pipe wrench or other tool
- Additional cut-outs and locations are available as engineering special, consult customer service
- LLP= Less Lock Protector



VR900

VR904

Specifications

Available sizes	11 Gauge (0.120" thick)
Material substrate	304 Series stainless steel standard, exceeding industry standards for corrosion resistance. Recommended for external applications.
Mounting hardware	<ul style="list-style-type: none"> ▪ For door thickness 1 3/4"-2 1/4" <ul style="list-style-type: none"> – 1/4"-20 X 1 1/4" and 1/4"-20 X 1 3/4" mounting screws with countersunk washers ▪ Can be mounted directly to Schlage L9000 Series ▪ Standard mounting - Welded studs fasten with pan head screws on opposite side of door ▪ Optional through bolt mounting - bolt through face of trim into device for added security

Dimensions

Width	Height	Through bolt pattern (4 holes)	Clearance grip to door	Projection
5 1/4"	11"	1 3/4" wide x 10" high	1 1/2"	1 7/8"

Finishes

BHMA	Description	Substrate	Finish
630	Satin Stainless	Stainless steel	US32D

Models are available with or without attractive black plastisol edge grip.

Custom finishes are available as engineering special, consult customer service.